

40-60 VERSA LIFT WITH 4 COUNTERWEIGHT SLABS

Slab Weight (kg)
1700

Number of Slabs
4

Standard Wheel Base (mm)
2490

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	900	18900	21000	23100	25200	27300
	1200	15800	17500	19300	21100	22900
	1500	13600	15100	16600	18100	19600
	1800	11900	13200	14600	15900	17200
	2100	10600	11800	13000	14100	15300

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	18000	20000	22100	24200	26300
	900	15100	16800	18600	20300	22000
	1200	13000	14500	16000	17500	19000
	1500	11400	12700	14100	15400	16700
	1800	10200	11300	12500	13700	14900
	2000	9700	10700	11900	13000	14100
	2100	9200	10200	11300	12300	13400
	2300	8800	9700	10700	11800	12800
	2400	8300	9300	10300	11200	12200
	2600	8000	8900	9800	10800	11700
	2700	7700	8600	9400	10300	11200
	2900	7400	8200	9100	9900	10800
3000	7100	7300*	7300*	7300*	7300*	

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	17400	19500	21500	23600	25700
	900	14600	16300	18000	19800	21500
	1200	12600	14100	15600	17000	18500
	1500	11000	12300	13600	15000	16300
	1800	9800	11000	12200	13300	14500

*****All Load Capacities are rated with the mast vertical***Regions marked by an * are limited by Structural Limitations**

40-60 VERSA LIFT WITH 3 COUNTERWEIGHT SLABS

Slab Weight (kg)
1700

Number of Slabs
3

Standard Wheel Base (mm)
2490

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	900	16700	18500	20400	22200	24000
	1200	14000	15500	17000	18600	20100
	1500	12000	13300	14600	16000	17300
	1800	10500	11700	12800	14000	15200
	2100	9400	10400	11400	12500	13500

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	15800	17600	19500	21300	23100
	900	13200	14800	16300	17800	19400
	1200	11400	12700	14100	15400	16700
	1500	10000	11200	12300	13500	14600
	1800	8900	10000	11000	12000	13100
	2000	8500	9400	10400	11400	12400
	2100	8100	9000	9900	10800	11800
	2300	7700	8600	9400	10300	11200
	2400	7300	8200	9000	9900	10700
	2600	7000	7800	8700	9400	10200
	2700	6800	7500	8300	9100	9800
	2900	6500	7200	8000	8700	9400
3000	6200	6900	7300*	7300*	7300*	

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	15200	17000	18800	20600	22400
	900	12700	14300	15800	17300	18900
	1200	11000	12300	13600	14900	16200
	1500	9700	10800	12000	13100	14200
	1800	8600	9600	10700	11700	12700

***All Load Capacities are rated with the mast vertical
***Regions marked by an * are limited by Structural Limitation

40-60 VERSA LIFT WITH 2 COUNTERWEIGHT SLABS

Slab Weight (kg)
1700

Number of Slabs
2

Standard Wheel Base (mm)
2490

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	900	14500	16100	17600	19200	20800
	1200	12100	13400	14700	16100	17400
	1500	10400	11500	12700	13800	15000
	1800	9100	10100	11100	12100	13100
	2100	8100	9000	9900	10800	11700

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	13600	15200	16700	18300	19900
	900	11400	12700	14100	15300	16600
	1200	9800	11000	12100	13200	14300
	1500	8700	9600	10600	11600	12600
	1800	7700	8600	9500	10300	11200
	2000	7300	8200	9000	9800	10700
	2100	6900	7800	8500	9300	10100
	2300	6600	7400	8200	8900	9700
	2400	6300	7100	7800	8500	9200
	2600	6100	6800	7400	8100	8800
	2700	5800	6500	7100	7800	8500
	2900	5600	6200	6800	7500	8100
3000	5400	6000	6600	7200	7300*	

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	13000	14600	16100	17700	19200
	900	10900	12200	13500	14800	16100
	1200	9400	10500	11700	12800	13900
	1500	8300	9300	10200	11200	12200
	1800	7300	8300	9100	10000	10900

***All Load Capacities are rated with the mast vertical
 ***Regions marked by an * are limited by Structural Limitations

40-60 VERSA LIFT WITH 1 COUNTERWEIGHT SLAB

Slab Weight (kg)
1700

Number of Slabs
1

Standard Wheel Base (mm)
2490

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	900	12200	13600	14900	16200	17500
	1200	10200	11300	12400	13600	14600
	1500	8800	9700	10700	11700	12600
	1800	7700	8600	9400	10200	11000
	2100	6900	7600	8300	9100	9800

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	11500	12700	14100	15300	16600
	900	9600	10700	11800	12900	14000
	1200	8300	9200	10200	11100	12000
	1500	7300	8100	8900	9700	10600
	1800	6500	7200	7900	8700	9400
	2000	6200	6800	7500	8200	8900
	2100	5800	6500	7200	7800	8500
	2300	5600	6200	6800	7400	8100
	2400	5300	5900	6500	7100	7700
	2600	5100	5700	6300	6800	7400
	2700	4900	5400	6000	6500	7100
	2900	4700	5200	5800	6300	6800
3000	4500	5000	5500	6000	6600	

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	10800	12200	13400	14700	16000
	900	9100	10200	11300	12300	13400
	1200	7800	8800	9700	10700	11600
	1500	6900	7700	8500	9300	10200
	1800	6100	6800	7600	8300	9100

*****All Load Capacities are rated with the mast vertical**

40-60 VERSA LIFT WITH 0 COUNTERWEIGHT SLABS

Slab Weight (kg)
1700

Number of Slabs
0

Standard Wheel Base (mm)
2490

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	900	10000	11100	12200	13200	14200
	1200	8400	9300	10200	11000	11900
	1500	7200	8000	8700	9500	10200
	1800	6300	7000	7700	8300	9000
	2100	5600	6200	6800	7400	8000

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	9300	10300	11300	12400	13400
	900	7800	8700	9500	10400	11200
	1200	6700	7400	8200	8900	9700
	1500	5900	6500	7200	7800	8500
	1800	5300	5800	6400	7000	7600
	2000	5000	5500	6100	6600	7200
	2100	4700	5300	5800	6300	6800
	2300	4500	5000	5500	6000	6500
	2400	4300	4800	5300	5800	6200
	2600	4100	4600	5000	5500	5900
	2700	3900	4400	4900	5300	5700
	2900	3800	4200	4600	5100	5500
3000	3700	4100	4500	4900	5300	

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	8700	9700	10700	11700	12800
	900	7300	8200	9000	9900	10700
	1200	6300	7000	7800	8500	9300
	1500	5500	6200	6800	7500	8100
	1800	4900	5500	6100	6700	7300

*****All Load Capacities are rated with the mast vertical**